


You select...
You
 We connect
 We

eWON 2001 Industrial Modem Router




Highlights

- Ethernet (RJ45) and serial (DB9) interfaces supporting numerous PLC protocols
- Embedded PSTN, ISDN, GSM/GPRS or EDGE modem
- Alarms management on PLC variables with notification (SMS, email, FTP put or trap SNMP)
- Configuration by embedded web pages or FTP upload
- 1 x digital input (alarm) and 1 x digital output
- Full industrial design (24 VDC Power supply, DIN Rail mounting)
- Optional: Data logging and reporting features
- Optional: Web HMI with animated synoptics

eWON 2001 is the Industrial Modem-Router for the machine builder, OEM, infrastructure, utilities, and system integrator markets, offering full remote access to any PLC or automation device through its serial or Ethernet port. Seamlessly integrated with the PLC programming environment, eWON 2001 still monitors and collects data into internal tags while PLC maintenance is performed. eWON 2001 has both Web and FTP servers embedded as well as an independent alarm management system.

Typical Applications

- Modem IP Router within an RAS (Remote Access Service) connection
- Remote access for PLC maintenance
- Alarm notification, remote diagnosis and remote maintenance/monitoring



Ethernet to Serial Gateways	MODBUS TCP to MODBUS RTU; XIP to UNITELWAY; EtherNet/IP™ to DF1; FINS TCP to FINS Hostlink; ISO TCP to PPI, MPI (S7) or PROFIBUS ¹ (S7) ; VCOM / ASCII
Data Acquisition Protocols	In MODBUS/RTU, MODBUS/TCP, Unitelway, DF1, PPI, MPI (S7), PROFIBUS ¹ (S7), FINS Hostlink, FINS TCP, EtherNet/IP™, ISO TCP, ASCII. Stored in 350 internal tags
Alarms	Alarms notification by email, FTP put and/or traps SNMP Threshold: low, lowlow, high,highhigh + deadband and activation delay Alarms logs in http and via FTP Alarms cycle: ALM, RTN, ACK and END
Router	PPP dial-in, Internet PPP dial-out on demand, IP filtering, IP forwarding, NAT, Port forwarding, Proxy, Routing table
Call Back	Direct callback through RAS connection on user request or on number of rings
RAS Connection	PPP (Point-to-Point) Protocol with PAP/CHAP security and data compression
Script	Script interpreter for Basic language with development tools
Synchronization	Embedded real-time clock, manual setup via http or automatic via NTP
File Management	FTP client and server for configuration, firmware update and data transfer
Web Site	Security: Basic authentication and session control. HTML standard, supports PDA browsers. eWON system and user customisable Web sites. SSI technology (Server Side Include) and Basic scripted ASP (Active Server Pages). HTTP server. Also HTTP client allowing HTML Get & Put requests onto remote HTTP servers.
Maintenance	SNMP V1 with MIB2 and/or via FTP files
Hardware	ARM processor @75Mhz, 8Mb SDRAM, 16Mb Flash, Din Rail Mounting Power supply 12 - 24VDC +/-20%, SELV; consumption: 3-6 watts 1x SUBD9 serial port RS232, RS422 & RS485 not isolated or MPI/PROFIBUS ¹ port isolated (limited to 1,5Mbits) 1x RJ45 Ethernet 10/100 baseTx; 1,5kV isolation 1x digital input: 0/24VDC; 3,5kV isolation 1x digital output: open collector 200mA@30VDC; 3,5 kV isolation Embedded modem: PSTN 56kbds or ISDN or Dual band GPRS or Quad band EDGE Operating Temperature range: 0° to 50°C, optional extended temperature range (-20 to 70°C on request) available, 80% humidity (no condensation) Dimensions : 120(Depth) x 105(Height) x 26(Width) mm; Weight : <300gr CE, UL labelled

Product Ref.: EW212xy	- x = 0 with serial port RS232, 422 ou 485	- x = 6 with MPI/PROFIBUS ¹ (S7) port
	- y = 3 ISDN EU modem (on request)	- y = 4 PSTN 56kbds modem
	- y = 5 GSM/GPRS EU modem	- y = 6 GSM/GPRS US modem
	- y = 7 EDGE quad band modem	

¹ A brief disturbance on the Profibus network can be caused by this eWON model when switching on/off. For a stand alone device, this is not a problem. But if the Profibus network is used for intercommunication between Profibus and Slave devices, the Siemens CPU might change into STOP mode if the network errors are not handled inside the CPU program (OB85 & OB86).

Your eWON distributor:



Postbus 3
6620 AA DREUMEL
tel. +31 (0)487-572719
fax +31 (0)487-573394
www.raster.com
info@raster.com

List of local distributors & partners



eWON s.a., part of ACT'L group, is a Belgian electronic company manufacturing the eWON product line. Since its launch in 2001, eWON became a worldwide market challenger for intelligent Ethernet gateways and industrial IP routers. Thanks to its growing market recognition, the eWON concept has become a reference and a quality standard for every major company in the industry.

www.ewon.biz